PR-855

85 Columns Dot Matrix Printer

Wider Paper, More Choice

85 columns printing width, ranging from the size of A3 to the size of name card

1 Original + 6 Copies

Sharp and clear documents right through the last copy

Power-efficient

More environmental adaptor supply, 0.5W on standby

High Reliability

500 million times of printhead life span, MTBF uo to 12,000 operating hours

PR-855

2 Years **Printer Warranty** (Printhead included)

ISO-9001 Manufactured by ISO Certified Plant

ISO 14001

RoHS compliant

REACH Ready

CE FC

PR-855
85 Columns Dot Matrix Printer

PRINT-RITE®

Printing system	serial dot matrix
Printing width	85 columns(1 column=2.54mm)

Printing speed

	character width	ultra-high speed (character/sec)	high speed (character/sec)	high density (character/sec)
English	10CPI	300	225	150
	12CPI	360	270	180
	15CPI	450	338	225

Resolution ratio	360 x 360dpi(max.)
Printing mode	two-way /one-way
Number of pins	24
Printhead life	up to 500 million strokes/wire
Line spacing	1/6 inch, 1/8 inch, n/60 inch, n/180 inch, n/360 inch
English typeface	the roman font /OCR-A /OCR-B
Chinese typeface	GB18030 Song Font
Character set	ASCII chararcter: 96 International character: 16 countries IBM character: 32 Chinese: GB18030 24 x 24 Bitmap Font (21887)
CPU frequency	64MHz
Input data buffer	128K
Interface	USB2.0 interface
Ribbon	fabric ribbon cartridge (black)—PR-855
Ribbon life	approx. 5 million characters
Mean time between failure	up to 12,000 hours (MTBF)
Power supply	+35V === 1.2A
Standby power	0.5W
Working environment	temperature:+5℃~+40℃ relative moisture:10%~80%(without condensation)
Compatible operating system	Windows 2000 Windows 7-11 Windows Vista Windows XP Linux (Ubuntu and Deepin)

Dimensions (WxDxH)	400mm x 230mm x 185mm
Weight	3.8Kg
Printing paper	width 56~297mm（single paper） 70~268mm(chain paper) length ≥58mm thickness 0.06~1.2mm A3 workable name card workable
Copy ability	up to 1 Original + 6 Copies
Emulation command	EPSON ESC/P: OKI emulation
Manual feed	manual feed
Feeding mode	pushing friction feeding /chain paper feeding
Feeding speed	maximum 3.43 inches/sec
Smart function	compensation of broken pin
Certification	ISO-9001, ISO-14001, RoHS, REACH, CE, FCC
Warranty	2 years printer warranty (printhead included)

Applications

- ☑ VAT special invoice
- ☑ VAT invoice
- ☑ local tax invoice
- ☑ bank note
- ☑ bank draft
- ☑ medical receipt
- ☑ e-ticket itinery for air transportation
- ☑ insurance policy
- ☑ delivery order
- ☑ invoice of telecom industry
- ☑ outdeliver order
- ☑ payment bill
- ☑ business statement
- ☑ more bills